

Cable Gland - CM, AC - PG Thread - Nickel-Plated BRASS



Part No.	Identification	Thread	Min. Cable Size	Max. Cable Size	Thread Length	Width (mm)	
DEL2701	CM8 AC9	PG-9	6	8	7	19	
DEL2702	CM8 long AC9	PG-9	6	8	15	19	
DEL2703	CM10 AC11	PG-11	8	10	7	22	
DEL2704	CM10 long AC11	PG-11	8	10	15	22	
DEL2705	CM12 AC13	PG-13	10	12	8	24	
DEL2706	CM12 long AC13	PG-13	10	12	15	24	
DEL2707	CM14 AC16	PG-16	12	14	8	27	
DEL2708	CM14 long AC16	PG-16	12	14	15	27	
DEL2709	CM18 AC21	PG-21	14	18	8	34	
DEL2710	CM18 long AC21	PG-21	14	18	15	34	
DEL2711	CM24 AC29	PG-29	18	24	8	42	
DEL2712	CM24 long AC29	PG-29	18	24	15	42	
DEL2713	CM30 AC36	PG-36	24	30	8	52	
DEL2714	CM30 long AC36	PG-36	24	30	15	52	
DEL2715	CM35 AC42	PG-42	30	35	10	62	
DEL2716	CM35 long AC42	PG-42	30	35	15	62	
DEL2717	CM40 AC48	PG-48	35	40	10	68	
DEL2718	CM40 long AC48	PG-48	35	40	15	68	
DEL2718	CM50 long 2 1/2"	2" 1/2	40	50	18	80	
DEL2720	CM60 long 3"	3"	40	60	20	100	
DEL2721	CM80 long 4"	4"	60	80	25	115	

Temp. Range: -40°C to 120°C
 Rating: IP 66
 Standards: NFC 68312