

Cable Gland - FMC "Perfect" - Metric Thread - Nickel Plated BRASS



| Part No. | Thread | Min. Cable Size (mm ²) | Max. Cable Size (mm ²) | Thread Length (mm) | Width (mm) | |
|------------|-------------|------------------------------------|------------------------------------|--------------------|------------|--|
| DEL50749EX | M12 x 1.5mm | 3 | 6 | 10 | 14 | |
| DEL50750EX | M16 x 1.5mm | 5 | 9 | 10 | 17 | |
| DEL50751EX | M20 x 1.5mm | 9 | 13 | 10 | 22 | |
| DEL50752EX | M25 x 1.5mm | 11 | 16 | 11 | 27 | |
| DEL50753EX | M32 x 1.5mm | 14 | 21 | 13 | 34 | |
| DEL50754EX | M40 x 1.5mm | 19 | 27 | 13 | 43 | |
| DEL50755EX | M50 x 1.5mm | 24 | 35 | 14 | 55 | |
| DEL50756EX | M63 x 1.5mm | 32 | 42 | 14 | 65 | |
| DEL5075BEX | M63 x 1.5mm | 38 | 48 | 14 | 65 | |

Temp. Range:
 -20°C to +80°C
 Rating: IP 68
 Certifications: DMT 99,
 ATEX E16, EN 60423