

# SCREWS, BOLTS, & THREADED ROD

SECTION

II

## THREADED ROD

This versatile threaded rod stock is easily cut to size, resistant to most chemicals, electrically insulating, non-magnetic, lightweight, low thermal conductivity, vibration and abrasion resistant.

Stock length is 2 feet. Longer lengths up to 8 feet available on special order.

We can cut to your length requirement with a nominal cutting charge.

Other plastic materials can be furnished on special order.

Request quote.

**METRIC Sizes  
Also Available**

Page 272

PVC (Polyvinyl Chloride) is an amorphous thermo-plastic material with excellent chemical resistance and dielectric properties. Good tensile, flexural and mechanical strength, low moisture absorption, exceptional dimensional stability and good flammability characteristics. Maximum service temperature 140° F. PVC has a good high strength to weight ratio. Rated UL94VO. Dark gray color. Stock lengths; 2 FT, 4 FT, 6 FT, and 8 FT. Special lengths can be cut to your length requirement for a nominal cutting charge. Please request quote.



## PVC THREADED RODS

Molded in Natural PVC

PART NUMBER	SCREW SIZE	THREAD
3800440TRPVC	4	440
3800632TRPVC	6	632
3800832TRPVC	8	832
3801024TRPVC	10	1024
3801032TRPVC	10	1032
3825020TRPVC	1/4	1/4-20
3831218TRPVC	5/16	5/16-18
3837516TRPVC	3/8	3/8-16
3850013TRPVC	1/2	1/2-13
3862511TRPVC	5/8	5/8-11
3875010TRPVC	3/4	3/4-10
3887509TRPVC	7/8	7/8-9
3810008TRPVC	1	1-8

## NYLON THREADED RODS

Molded in Natural Nylon 6/6

PART NUMBER	SCREW SIZE	THREAD
3800440TR	4	440
3800632TR	6	632
3800832TR	8	832
3801024TR	10	1024
* 3801032TR	10	1032
* 3825020TR	1/4	1/4-20
* 3831218TR	5/16	5/16-18
* 3837516TR	3/8	3/8-16
* 3850013TR	1/2	1/2-13
3862511TR	5/8	5/8-11
3875010TR	3/4	3/4-10
3887509TR	7/8	7/8-9
3810008TR	1	1-8

\* These sizes are available in natural Acetal material, contact sales for price.