




- Use with Flexible Armored Cable (BX) and Flexible Metallic Conduit (FMC), to insulate rough cut conduit ends.
- Chamfered lead-in allows for fast installation.
- Suitable for installation at temperatures up to 194°F (90°C) and as low as -40°F (-40°C).
- Size-marked for easy identification.



Heyco® Armor Bushings

WILL FIT THESE ARMORED CABLES (AWG/CONDUCTORS)	PART NO.	DESCRIPTION	PART DIMENSIONS					
			A Inside Diameter		B Head Diameter		C Overall Height	
			in.	mm.	in.	mm.	in.	mm.
14/2, 14/3, 12/2, 12/3	2264	AB 0	.37	9,4	.68	17,3	.58	14,7
14/4, 6/1, 4/1	2265	AB 1	.44	11,2	.70	17,8	.63	16,0
12/4, 10/2, 10/3, 2/1	2266	AB 2	.57	14,0	.85	21,6	.61	15,5
	2281	AB Orange*	.58	14,7	.90	22,9	.50	12,7
10/4, 8/2, 8/3, 1/1	2267	AB 3	.73	18,5	1.02	25,9	.70	17,8

Standard color red except as noted.
 *This part is not UL or CSA certified.



2264/2265



2266/2267

Quick
Specs

Material
Temperature Range

High Dielectric Polyethylene
-40°F (-40°C) to 194°F (90°C)