





## Heyclip™ "J" Style Wire Clips Adhesive-Backed

- Low profile design perfect when clearance is a concern.
- Made of PVC with large adhesive base for greater holding power.
- Quick and easy installation—simply peel off backing and press into place. Clips should be stored at a temperature of 60°F (16°C) to 80°F (27°C).
- Multiple sizes ranging from .125" (3,2 mm) to .375" (9,5 mm).
- Rated static loads apply for parts fastened to a flat, clean, dry surface used within a temperature range of -20°F (-29°C) to 150°F (66°C).
- Apply to a clean dry surface.

MAX. BUNDLE DIAMETER		PART NO.	DESCRIPTION	RATED STATIC LOAD (lb.)	PART DIMENSIONS					
in.	mm.				A		B		C	
.125	3,2	3839	WCJA 125-750	3/4	1.00	25,4	1.00	25,4	.28	7,1
.187	4,7	3840	WCJA 187-1000	1	1.00	25,4	1.25	31,8	.32	8,4
.250	6,4	3841	WCJA 250-1125	1-1/8	1.00	25,4	1.50	38,1	.40	10,2
.312	7,9	3842	WCJA 312-1750	1-3/4	1.25	31,8	1.75	44,5	.48	12,2
.375	9,5	3843	WCJA 375-2000	2	1.25	31,8	2.00	50,8	.54	13,7

Standard color clear.



## Heyclip™ "C" Style Wire Clip Adhesive-Backed

- Low profile design perfect when clearance is a concern.
- Made of PVC with large adhesive base for greater holding power.
- Quick and easy installation—simply peel off backing and press into place. Recommended storage temperature from 60°F (16°C) to 80°F (27°C), and approximate relative humidity of 50%.
- Install and use at a temperature range of -20° (-29°C) to 150°F (66°C).
- Apply to a clean dry surface.

MAX. BUNDLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS									
in.	mm.			A		B		C		D		E	
.500	12,7	3794	WCCA 500	.48	12,3	.57	14,6	1.00	25,4	.75	19,1	.05	1,3

Standard color white.

