

“Stay Connected” with



Bushings, Grommets, HEYcaps & Plugs

a PennEngineering® Company





Heyco® Shorty Universal Bushings

Single Locking Step for Panel Thickness up to .062" (1,6 mm)
Mounting Hole Diameter Range: .500" (12,7 mm) to 1.093" (27,8 mm)

| MOUNTING HOLE DIAMETER | | PART NO. | DESCRIPTION | PART DIMENSIONS | | | | | |
|------------------------|------|-------------|-------------|-----------------|-------------------------|------|-----------------|-----|------------------|
| in. | mm. | | | Black | Maximum Inside Diameter | | A Head Diameter | | B Overall Height |
| | | | | in. | mm. | in. | mm. | in. | mm. |
| .500 | 12,7 | 2858 | SUB 500 | .31 | 7,6 | .60 | 15,2 | .25 | 6,4 |
| .625 | 15,9 | 2861 | SUB 625 | .44 | 11,1 | .73 | 18,5 | | |
| .750 | 19,1 | 2862 | SUB 750 | .50 | 12,7 | .86 | 21,8 | | |
| .875 | 22,2 | 2863 | SUB 875 | .56 | 14,3 | .94 | 23,8 | | |
| 1.000 | 25,4 | 2864 | SUB 1000 | .75 | 19,0 | 1.06 | 27,0 | | |
| 1.093 | 27,8 | 2158 | SUB 1093 | .81 | 20,6 | 1.16 | 29,4 | | |

Standard color black. Consult Heyco for white and other colors.





- For use in mounting panels **.062" (1,6 mm) and thinner.**
- Absorb vibration and cushion and insulate cables, tubing, hoses or shafts with limited internal clearance.
- Flexible shutters adjust to accommodate and support any shape from .125" (3,2 mm) to a maximum inside diameter of .812" (20,6 mm).
- Fingertip pressure snap-locks the bushing into its mounting hole.
- **See Quick Specs on 6-11.**

Heyco® Thick Panel Universal Bushings

Multiple Locking Steps for Panel Thickness up to .250" (6,4 mm)
Mounting Hole Diameter Range: .500" (12,7 mm) to 1.500" (38,1 mm)

| MOUNTING HOLE DIAMETER | | PART NO. | DESCRIPTION | PART DIMENSIONS | | | | | |
|------------------------|------|-------------|-------------|-----------------|-------------------------|------|-----------------|-----|------------------|
| in. | mm. | | | Black | Maximum Inside Diameter | | A Head Diameter | | B Overall Height |
| | | | | in. | mm. | in. | mm. | in. | mm. |
| .500 | 12,7 | 3001 | UBT 500 | .31 | 7,6 | .60 | 15,2 | .55 | 13,8 |
| .625 | 15,9 | 3118 | UBT 625* | .44 | 11,1 | .73 | 18,5 | .51 | 13,0 |
| .750 | 19,1 | 3119 | UBT 750* | .50 | 12,7 | .84 | 21,4 | .55 | 13,8 |
| .875 | 22,2 | 3120 | UBT 875 | .56 | 14,3 | .94 | 23,8 | | |
| 1.000 | 25,4 | 3121 | UBT 1000 | .75 | 19,1 | 1.06 | 27,0 | | |
| 1.093 | 27,8 | 3002 | UBT 1093 | .81 | 20,6 | 1.16 | 29,5 | | |
| 1.375 | 34,9 | 3003 | UBT 1375 | 1.00 | 25,4 | 1.49 | 37,8 | .56 | 14,2 |
| 1.500 | 38,1 | 3122 | UBT 1500 | 1.06 | 26,9 | 1.61 | 40,9 | | |

Standard color black. Consult Heyco for white and other colors.
*Single Locking Step for Panel Thickness up to .250" (6,4 mm).



- For use in mounting panels up to **.250" thick.**
- Flexible shutters to absorb vibration on the inside diameter.
- Insulate and mechanically protect electrical and telecommunications cables, tubing, hose, rope, and utility lines.
- Withstand a push back force of 35 pounds.
- Locking fingers snap into holes with fingertip pressure.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Available in multiple sizes for use in .500" (12,7 mm) to 1.500" (38,1 mm) diameter holes.
- **See Quick Specs on 6-11.**