



- Grommet Strips protect against damage from sharp panel edges.
- Ideal for tight radii or irregular panel holes and cut-outs.



Un-serrated



Serrated


## Heyco® Continuous Grommet Rolls Polyethylene 100' (30.5 M) Roll

FIT PANEL THICKNESS RANGE				PART NO.		DESCRIPTION	PART DIMENSIONS					
Minimum		Maximum		Natural	Black		A Overall Height		B Bottom Thickness		C Bottom Width	
in.	mm.	in.	mm.			in.	mm.	in.	mm.	in.	mm.	
<b>Un-serrated</b>												
.037	0,9	.071	1,8	<b>12391</b>	<b>12391B</b>	PGS-071-100'	.172	4,4	.031	0,8	.109	2,8
.072	1,8	.105	2,7	<b>12392</b>	<b>12392B</b>	PGS-105-100'						
.106	2,7	.164	4,2	<b>12393</b>	<b>12393B</b>	PGS-164-100'	.188	4,8	.047	1,2	.156	4,0
<b>Un-serrated, with Adhesive</b>												
.037	0,9	.071	1,8	<b>12395</b>	<b>12395B</b>	PGSG-071-1-100'	.160	4,1	.025	0,6	.060	1,5
				<b>12396</b>	<b>12396B</b>	PGSG-071-2-100'	.172	4,4	.031	0,8	.109	2,8
.072	1,8	.105	2,7	<b>12397</b>	<b>12397B</b>	PGSG-105-100'	.172	4,4	.031	0,8	.109	2,8
.106	2,7	.164	4,2	<b>12398</b>	<b>12398B</b>	PGSG-164-100'	.188	4,8	.047	1,2	.156	4,0
<b>Serrated</b>												
.026	0,7	.036	0,9	<b>12399</b>	<b>12399B</b>	SPGS-036-100'	.125	3,2	.031	0,8	.031	0,8
.037	0,9	.071	1,8	<b>12400</b>	<b>12400B</b>	SPGS-071-100'	.172	4,4	.031	0,8	.109	2,8
.072	1,8	.105	2,7	<b>12401</b>	<b>12401B</b>	SPGS-105-100'						
.106	2,7	.164	4,2	<b>12402</b>	<b>12402B</b>	SPGS-164-100'	.188	4,8	.047	1,2	.156	4,0
<b>Serrated, with Adhesive</b>												
.037	0,9	.071	1,8	<b>12405</b>	<b>12405B</b>	SPGSG-071-1-100'	.160	4,1	.025	0,6	.060	1,5
				<b>12406</b>	<b>12406B</b>	SPGSG-071-2-100'	.172	4,4	.031	0,8	.109	2,8
.072	1,8	.105	2,7	<b>12407</b>	<b>12407B</b>	SPGSG-105-1-100'	.172	4,4	.031	0,8	.109	2,8

## Nylon 100' (30.5 M) Roll





UN-SERRATED



SERRATED

FIT PANEL THICKNESS RANGE				PART NO.		DESCRIPTION	PART DIMENSIONS					
Minimum		Maximum		Natural	Black		A Overall Height		B Bottom Thickness		C Bottom Width	
in.	mm.	in.	mm.			in.	mm.	in.	mm.	in.	mm.	
<b>Un-serrated</b>												
.026	0,7	.036	0,9	<b>12411</b>	<b>12411B</b>	NGS-036-100'	.13	3,2	.03	0,8	.03	0,8
.037	0,9	.071	1,8	<b>12412</b>	<b>12412B</b>	NGS-071-100'	.17	4,4	.03	0,8	.11	2,8
<b>Un-serrated, with Adhesive</b>												
.037	0,9	.071	1,8	<b>12416</b>	<b>12416B</b>	NGSG-071-100'	.17	4,4	.03	0,8	.11	2,8
.072	1,8	.105	2,7	<b>12417</b>	<b>12417B</b>	NGSG-105-100'						
.106	2,7	.164	4,2	<b>12418</b>	<b>12418B</b>	NGSG-164-100'	.19	4,8	.05	1,2	.16	4,0
<b>Serrated</b>												
.026	0,7	.036	0,9	<b>12419</b>	<b>12419B</b>	SNGS-036-100'	.13	3,2	.03	0,8	.01	0,8
.037	0,9	.071	1,8	<b>12420</b>	<b>12420B</b>	SNGS-071-100'	.17	4,4	.03	0,8	.11	2,8
.072	1,8	.105	2,7	<b>12421</b>	<b>12421B</b>	SNGS-105-100'						
.106	2,7	.164	4,2	<b>12422</b>	<b>12422B</b>	SNGS-164-100'	.19	4,8	.05	1,2	.16	4,0
<b>Serrated, with Adhesive</b>												
.037	0,9	.071	1,8	<b>12426</b>	<b>12426B</b>	SNGSG-071-100'	.17	4,4	.03	0,8	.11	2,8
.072	1,8	.105	2,7	<b>12427</b>	<b>12427B</b>	SNGSG-105-100'						

Standard color natural. Black available by special order only.



Quick Specs

Material	Polyethylene or Nylon
Flammability Rating	94HB (Nylon only)
Temperature Range	-40°F (-40°C) to 149°F (65°C) (Polyethylene) -40°F (-40°C) to 185°F (85°C) (Nylon)